

## Cold Drawing Bar

Flat (みがき平)

size mm t x w	kg/m	SS400	S45C	size mm t x w	kg/m	SS400	S45C	size mm t x w	kg/m	SS400	S45C
		length	length			length	length			length	length
3 × 9	0.212	3 ●		6 × 25	1.178	3 ●	4 ●	9 × 250	17.66	4 ○	4 ○
3 × 10	0.236	3 ●		6 × 32	1.507	4 ●	4 ●	9 × 300	21.2	4 ○	4 ○
3 × 12	0.283	3 ●		6 × 38	1.790	4 ●	4 ●	9 × 350	24.73	4 ○	
3 × 13	0.306	3 ●	2 ●	6 × 40	1.884	4 ●		9 × 400	28.26	4 ○	
3 × 16	0.377	3 ●	3 ●	6 × 44	2.072	4 ●	4 ●	10 × 12	0.942	4 ●	
3 × 19	0.447	3 ●	3 ●	6 × 50	2.355	4 ●	4 ●	10 × 15	1.178	4 ●	
3 × 22	0.518	3 ●	3 ●	6 × 60	2.826	4 ●	4 ●	10 × 16	1.256	4 ●	
3 × 25	0.589	3 ●	3 ●	6 × 65	3.062	4 ●	4 ●	10 × 20	1.57	4 ●	
3 × 32	0.754	4 ●	4 ●	6 × 75	3.533	4 ●	4 ●	10 × 25	1.963	4 ●	
3 × 38	0.895	4 ●	4 ●	6 × 90	4.239	4 ●	4 ●	10 × 30	2.355	4 ●	
3 × 50	1.178	4 ●	4 ●	6 × 100	4.710	4 ●	4 ●	10 × 32	2.512	4 ●	4 ●
4 × 10	0.314	2 ●		6 × 125	5.888	4 ●	4 ●	10 × 38	2.983	4 ●	4 ●
4 × 13	0.408	2 ●		6 × 150	7.065	4 ●	4 ●	10 × 40	3.14	4 ●	
4 × 16	0.502	3 ●		6 × 180	8.478	4 ●		10 × 50	3.925	4 ●	4 ●
4 × 19	0.597	3 ●		6 × 200	9.42	4 ●		10 × 60	4.71	4 ●	
4 × 22	0.691	3 ●		6 × 250	11.78	4 ○		10 × 65	5.103	4 ●	
4 × 25	0.785	3 ●		6 × 300	14.13	4 ○		10 × 75	5.888	4 ●	
4 × 32	1.005	4 ●		6 × 350	16.49	4 ○		10 × 90	7.065	4 ●	
4.5 × 9	0.318	3 ●		6 × 400	18.84	4 ○		10 × 100	7.85	4 ●	
4.5 × 13	0.459	3 ●	3 ●	8 × 10	0.628	3 ●		10 × 125	9.813	4 ●	
4.5 × 16	0.565	3 ●	3 ●	8 × 12	0.754	4 ●		10 × 150	11.78	4 ●	
4.5 × 19	0.671	3 ●	3 ●	8 × 13	0.816	3 ●		10 × 200	15.7	4 ●	
4.5 × 22	0.777	3 ●	3 ●	8 × 16	1.005	3 ●		10 × 250	19.63	4 ○	
4.5 × 25	0.883	3 ●	4 ●	8 × 19	1.193	3 ●		10 × 300	23.55	4 ○	
4.5 × 32	1.13	4 ●	4 ●	8 × 22	1.382	4 ●		12 × 16	1.507	4 ●	4 ●
4.5 × 38	1.342	4 ●	4 ●	8 × 25	1.570	4 ●		12 × 19	1.79	4 ●	4 ●
4.5 × 50	1.766	4 ●	4 ●	8 × 30	1.884	4 ●		12 × 20	1.884	4 ●	
4.5 × 65	2.296	4 ●		8 × 32	2.010	4 ●		12 × 22	2.072	4 ●	4 ●
4.5 × 100	3.533	4 ●		8 × 40	2.512	4 ●		12 × 25	2.355	4 ●	4 ●
5 × 10	0.393	2 ●		8 × 50	3.140	4 ●		12 × 32	3.014	4 ●	4 ●
5 × 13	0.51	3 ●		9 × 12	0.848	4 ●		12 × 38	3.58	4 ●	4 ●
5 × 16	0.628	3 ●		9 × 13	0.918	4 ●		12 × 44	4.145	4 ●	4 ●
5 × 19	0.746	3 ●		9 × 16	1.130	4 ●	4 ●	12 × 50	4.71	4 ●	4 ●
5 × 22	0.864	3 ●		9 × 19	1.342	4 ●	4 ●	12 × 60	5.652	4 ●	4 ●
5 × 25	0.981	3 ●		9 × 22	1.554	4 ●	4 ●	12 × 65	6.123	4 ●	4 ●
5 × 30	1.178	4 ●		9 × 25	1.766	4 ●	4 ●	12 × 75	7.065	4 ●	4 ●
5 × 32	1.256	4 ●		9 × 32	2.261	4 ●	4 ●	12 × 90	8.478	4 ●	4 ●
5 × 38	1.492	4 ●		9 × 38	2.685	4 ●	4 ●	12 × 100	9.42	4 ●	4 ●
5 × 44	1.727	4 ●		9 × 44	3.109	4 ●	4 ●	12 × 125	11.78	4 ●	4 ●
5 × 50	1.963	4 ●		9 × 50	3.533	4 ●	4 ●	12 × 150	14.13	4 ●	4 ●
6 × 9	0.424	3 ●		9 × 60	4.239	4 ●	4 ●	12 × 180	16.96	4 ●	
6 × 10	0.471	3 ●		9 × 65	4.592	4 ●	4 ●	12 × 200	18.84	4 ●	4 ●
6 × 12	0.565	3 ●	4 ●	9 × 75	5.299	4 ●	4 ●	12 × 250	23.55	4 ○	4 ○
6 × 16	0.754	3 ●	4 ●	9 × 90	6.359	4 ●	4 ●	12 × 300	28.26	4 ○	4 ○
6 × 19	0.895	3 ●	4 ●	9 × 100	7.065	4 ●	4 ●	12 × 350	32.97	4 ○	
6 × 20	0.942	3 ●		9 × 125	8.831	4 ●	4 ●	12 × 400	37.68	4 ○	
6 × 22	1.036	3 ●	4 ●	9 × 150	10.60	4 ●	4 ●	15 × 20	2.355	4 ●	4 ●
				9 × 180	12.72	4 ●					
				9 × 200	14.13	4 ●	4 ●				

size : mm length : m

● : Thai stock ○ : Jpn stock



Cold Drawing Bar

Flat (みがき平)

size mm t x w	kg/m	SS400	S45C
		length	length
16 x19	2.386	4 ●	4 ●
16 x20	2.512	4 ●	
16 x22	2.763	4 ●	4 ●
16 x25	3.14	4 ●	4 ●
16 x32	4.019	4 ●	4 ●
16 x38	4.773	4 ●	4 ●
16 x44	5.526	4 ●	4 ●
16 x50	6.28	4 ●	4 ●
16 x60	7.536	4 ●	4 ●
16 x65	8.164	4 ●	4 ●
16 x75	9.42	4 ●	4 ●
16 x90	11.3	4 ●	4 ●
16 x100	12.56	4 ●	4 ●
16 x125	15.7	4 ●	4 ●
16 x150	18.84	4 ●	4 ●
16 x180	22.61	4 ●	
16 x200	25.12	4 ●	4 ●
16 x250	31.4	4 ○	4 ○
16 x300	37.68	4 ●	4 ○
16 x350	43.96	4 ○	
16 x400	50.24	4 ○	
19 x22	3.281	4 ●	4 ●
19 x25	3.729	4 ●	4 ●
19 x32	4.773	4 ●	4 ●
19 x38	5.668	4 ●	4 ●
19 x44	6.563	4 ●	4 ○
19 x50	7.458	4 ●	4 ●
19 x60	8.949	4 ●	4 ●
19 x65	9.695	4 ●	4 ●
19 x75	11.19	4 ●	4 ●
19 x90	13.42	4 ●	4 ●
19 x100	14.92	4 ●	4 ●
19 x125	18.64	4 ●	4 ●
19 x150	22.37	4 ●	4 ●
19 x180	26.85	4 ●	
19 x200	29.83	4 ●	4 ●
19 x250	37.29	4 ○	4 ○
19 x300	44.75	4 ○	4 ○
19 x350	52.2	4 ○	
19 x400	59.66	4 ○	
22 x25	4.318	4 ●	4 ●
22 x32	5.526	4 ●	4 ●
22 x38	6.563	4 ●	4 ●
22 x44	7.599	4 ●	4 ●
22 x50	8.635	4 ●	4 ●
22 x60	10.36	4 ●	
22 x65	11.23	4 ●	4 ●
22 x75	12.95	4 ●	4 ●
22 x90	15.54	4 ●	
22 x100	17.27	4 ●	4 ●

size mm t x w	kg/m	SS400	S45C
		length	length
22 x125	21.59	4 ●	4 ●
22 x150	25.91	4 ●	4 ●
22 x180	31.09	4 ○	
22 x200	34.54	4 ●	4 ●
22 x250	43.18	4 ○	
22 x300	51.81	4 ○	
22 x350	60.45	4 ○	
22 x400	69.08	4 ○	
25 x32	6.28	4 ●	4 ●
25 x38	7.458	4 ●	4 ●
25 x44	8.635	4 ●	4 ●
25 x50	9.813	4 ●	4 ●
25 x60	11.78	4 ●	4 ●
25 x65	12.76	4 ●	4 ●
25 x75	14.72	4 ●	4 ●
25 x90	17.66	4 ●	4 ●
25 x100	19.63	4 ●	4 ●
25 x125	24.53	4 ●	4 ●
25 x150	29.44	4 ●	4 ●
25 x180	35.33	4 ●	
25 x200	39.25	4 ●	4 ●
25 x250	49.06	4 ●	4 ○
25 x300	58.88	4 ○	4 ○
25 x350	68.69	4 ○	
25 x400	78.5	4 ○	
30 x50	11.78	4 ●	4 ●
30 x65	15.31	4 ●	4 ●
30 x75	17.66	4 ●	4 ●
30 x100	23.55	4 ●	4 ●
30 x125	29.44	4 ●	4 ●
30 x150	35.33	4 ●	4 ●
30 x200	47.1	4 ●	
30 x250	58.88	4 ○	
30 x300	70.65	4 ○	
30 x350	82.43	4 ○	
30 x400	94.2	4 ○	
32 x50	12.56	4 ●	4 ●
32 x65	16.33	4 ●	4 ●
32 x75	18.84	4 ●	4 ●
32 x100	25.12	4 ●	4 ●
32 x125	31.4	4 ●	4 ●
32 x150	37.68	4 ●	4 ●
32 x200	50.24	4 ●	
32 x250	62.8	4 ○	
32 x300	75.36	4 ○	
32 x350	87.92	4 ○	
32 x400	100.84	4 ○	

size mm t x w	kg/m	SS400	S45C
		length	length
38 x50	14.92	4 ●	4 ●
38 x65	19.39	4 ●	4 ●
38 x75	22.37	4 ●	4 ●
38 x100	29.83	4 ●	4 ●
38 x125	37.29	4 ●	4 ●
38 x150	44.75	4 ●	4 ●
38 x200	59.66	4 ●	
38 x250	74.58	4 ○	
38 x300	89.49	4 ○	
38 x350	104.41	4 ○	
38 x400	119.32	4 ○	
50 x65	25.51	4 ●	4 ●
50 x75	29.44	4 ●	4 ●
50 x100	39.25	4 ●	4 ●
50 x125	49.09	4 ●	
50 x150	58.88	4 ●	
50 x200	78.5	4 ○	
50 x250	98.13	4 ○	
50 x300	117.75	4 ○	



SS400 CD BARS : Raw materials  
SGD3, AISI1018, SWRM8~10, SGD1, SS400 etc.