

Cold Drawing Bar

Round (みがき丸棒)



size mm Φ	kg/m	SS400	S45C	SCM435	SCM415	S45CF	S45CHT	S45C-G	SK4F-G
		length	length	length	length	length	length	length	length
3	0.055	2 ◎							2 ○
4	0.099	2 ◎	2 ◎						2 ○
5	0.154	3 ◎	3 ◎	2 ◎	3 ◎				2 ○
6	0.222	3 ◎	3 ◎	3 ◎	3 ◎				2 ○
7	0.302	4 ◎	4 ◎	3 ◎	3 ◎				2 ○
8	0.395	4 ◎	4 ◎	3 ◎	3 ◎	3 ◎			2 ○
9	0.499	4 ◎	4 ◎	3 ◎	3 ◎	3 ◎			2 ○
10	0.617	4 ◎	4 ◎	3 ◎	3 ◎	3 ◎	3 ○	3 ○	2 ◎
11	0.746	4 ◎	4 ◎	3 ◎	3 ◎	3 ◎			2 ◎
12	0.888	4 ◎	4 ◎	3 ◎	3 ◎	3 ○	3 ○	3 ○	2 ◎
13	1.042	4 ◎	4 ◎	3 ◎	3 ◎	3 ○	3 ○		2 ◎
14	1.208	4 ◎	4 ◎	3 ◎	3 ◎	3 ○	3 ○		2 ◎
15	1.387	4 ◎	4 ◎	3 ◎	3 ◎	3 ○	3 ○	3 ○	2 ◎
16	1.578	4 ◎	4 ◎	3 ◎	3 ◎	3 ◎	3 ○	3 ○	2 ◎
17	1.782	4 ◎	4 ◎	3 ◎	3 ◎	3 ○	3 ○	3 ○	2 ◎
18	1.998	4 ◎	4 ◎	3 ◎	3 ◎	3 ○	3 ○		2 ◎
19	2.226	4 ◎	4 ◎	3 ◎	3 ◎	3 ○	3 ○		2 ◎
20	2.466	4 ◎	4 ◎	3 ◎	3 ◎	3 ○	3 ○	3 ○	2 ◎
21	2.719	4 ◎	4 ◎	3 ◎	3 ◎	3 ○	3 ○		
22	2.984	4 ◎	4 ◎	3 ◎	3 ◎	3 ○	3 ○	3 ○	2 ◎
23	3.261	3 ◎	3 ◎	3 ◎	3 ◎	3 ○			2 ◎
24	3.551	4 ◎	3 ◎	3 ◎	3 ◎	3 ○	3 ○		2 ◎
25	3.853	4 ◎	4 ◎	3 ◎	3 ◎	3 ○	3 ○	3 ○	2 ◎
26	4.168	3 ◎	3 ◎	3 ○	3 ○	3 ○	3 ○		2 ◎
27	4.495	3 ○	3 ◎	3 ◎	3 ○				
28	4.834	3 ◎	3.1 ◎	3 ◎	3 ◎	3 ◎	3 ○		2 ◎
29	5.185	3 ◎							
30	5.549	3 ◎	3 ◎	3 ◎	3 ◎	3 ○	3 ○	3 ○	2 ◎
32	6.313	3 ◎	3 ◎	3 ◎	3 ○	3 ○	3 ○		2 ◎
33	6.714	3 ○	3.2 ◎						
34	7.127	3 ◎	3 ◎	3 ◎	3 ○	3 ○	3 ○		
35	7.553	3.1 ◎	3.1 ◎	3 ◎	3 ◎	3 ○	3.2 ○	3 ○	2 ○
36	7.99	3 ◎	3 ◎	3 ◎	3 ◎	3 ○	3 ○		
38	8.903	3 ◎	3 ◎	3 ○	3 ○	3 ○	3.1 ○		
40	9.865	3 ◎	3 ◎	3.2 ◎	3 ◎	3 ○	3 ○	3 ○	2 ○
42	10.88	3 ◎	3 ◎			3 ○	3.1 ○		
44	11.94	3 ○	2.9 ◎						
45	12.48	3.1 ◎	3 ◎	3.3 ◎	3 ○		3.3 ○	3 ○	
46	13.05	2.9 ○	2.9 ◎				3.1 ○		
48	14.21	2.9 ◎	2.9 ◎						
50	15.41	3.2 ◎	3.2 ◎	3.2 ○	3.5 ○		3.5 ○	3 ○	2 ○
55	18.65	3.2 ◎	3 ◎						
60	22.2	3.1 ◎	3.1 ◎						
65	26.05	3.1 ◎	3.1 ◎						
70	30.21	3.3 ◎	3.3 ◎						
75	34.68	3.3 ○	3.3 ◎						
80	39.46	3.3 ◎	3.3 ◎						
85	44.54	3.3 ○	3.3 ◎						
90	49.94	3.3 ○	3.2 ◎						
95	55.64	3.3 ○	3.2 ◎						
100	61.65	3.2 ○	3.2 ◎						
110	74.6	3.5 ○	3.1 ◎						
115	81.5	3.2 ○	3.2 ○						
120	88.78	3.4 ○	3.1 ◎						
130	104.2	3.3 ○	3.3 ○						

inch

size mm Φ	kg/m	SS400	S45C
		length	length
6.35	0.249	3 ◎	4 ◎
9.52	0.559	4 ◎	
11.11	0.761	4 ◎	
12.7	0.994	4 ◎	4 ◎
14.28	1.257	4 ◎	
15.87	1.553	3 ◎	
19.05	2.237	4 ◎	
22.22	3.044	4 ◎	4 ◎
25.4	3.978	3 ◎	3 ◎

0.2mm size up

size mm Φ	kg/m	S45C
		length
7.2	0.32	3 ○
8.2	0.415	3 ○
9.2	0.522	3 ○
10.2	0.641	3 ○
12.2	0.918	3 ○
13.2	1.074	3 ○
14.2	1.243	3 ○
15.2	1.424	3 ○
16.2	1.618	3 ○
17.2	1.824	3 ○
18.2	2.042	3 ○
19.2	2.273	3 ○
20.2	2.516	3 ○
23.2	3.318	3 ○
24.2	3.611	3 ○
25.2	3.915	3 ○
26.2	4.232	3 ○
28.2	4.903	3 ○
30.2	5.623	3 ○
32.2	6.393	3 ○
35.2	7.639	3 ○
40.2	9.963	3 ○
45.2	12.6	3 ○
50.2	15.54	3 ○



size : mm length : m

◎ : Thai stock ○ : Jpn stock